

# P1.90

## P1.90 | PATH LIGHT

### CATEGORY

LED Path Light

### LED LIFE EXPECTANCY | WARRANTY

TM-21 data: Greater than **80,000 hours** (20+ years at 8 hours a day)

20 Year Warranty


We run our fixtures **40%** cooler than LM-80 testing standards



### SPECIFICATIONS

APPLICATION	CONSTRUCTION	DRIVER SYSTEM	INPUT POWER	INSTALLATION	LEAD WIRES	CRI	CERTIFICATION
Pathway Walkway Patios Small Areas	6061 Aluminum	Internal Driver	10.5-18 VAC	Ground Stake Included	UL1429 22 AWG Tinned Copper Wire 72 Inch Length	80	UL1838 Low Voltage Landscape Lighting

### PRODUCT DIMENSIONS



### WATTS / VA / LUMENS

WATTS / VA / LUMENS

2W/5VA - 230lm

### BEAM SPREAD & FINISH

BEAM SPREAD

120°

FINISH

Stainless Steel (SSA)  
Architectural Bronze  
(AB) Black (BLK)

### POWER CONSUMPTION

COLOR	TEMPERATURE	VA
Yellow	3000K	2
Light Yellow	2700K	2
White	5000K	2
Amber	AMB*	1
Blue	BLU	2
Blue-Black	RBL	2
Green	GRN	2
Red	RED*	1

INDICATES STOCKED ITEMS

### ADDITIONAL INFO

- Built in USA | Tampa, FL
- For custom light output, contact your sales associate
- \*Color Temperature Amber and Red are not Turtle Friendly; see our Turtle Friendly fixtures for more information

### PHOTOMETRICS

\*Complete IES files furnished upon request.

### FEATURES

- Overdesigned heat sink and thermal management for longevity and consistency
- Dedicated LED fixtures
- Machined Metal Ingot, not Cast Material
- Proprietary design-enhanced and robust driver technology
- Remarkably tight binning process. 2-step MacAdam ellipse to ensure consistent light output and no variant light
- Surge protection built into every driver

