

P12

P12 | PATH LIGHT



CATEGORY

LED Path Light

LED LIFE EXPECTANCY | WARRANTY

TM-21 data: Greater than **80,000 hours** (20+ years at 8 hours a day)

20 Year Warranty


We run our fixtures **40%** cooler than LM-80 testing standards



SPECIFICATIONS

APPLICATION	CONSTRUCTION	DRIVER SYSTEM	INPUT POWER	INSTALLATION	LEAD WIRES	CRI	CERTIFICATION
Pathway Walkway Patios Small/Large Areas	6061 Aluminum	External Driver	10.5-18 VAC	LV180 Ground Stake included	ULECC 18 AWG Tinned Copper Wire 46 inch length	80	UL1838 Low Voltage Landscape Lighting

PRODUCT DIMENSIONS



PHOTOMETRICS

*Complete IES files furnished upon request

WATTS / VA / LUMENS

WATTS / VA / LUMENS
2W/5VA - 230lm

BEAM SPREAD & FINISH

BEAM SPREAD	FINISH
120°	Black (BLK) Architectural Bronze (AB) Stainless Steel Aluminum (SSA)

POWER CONSUMPTION

COLOR	TEMPERATURE	VA
Yellow	3000K	5
Light Yellow	2700K	5
White	5000K	5
Orange	AMB*	6
Blue	BLU	5
Dark Blue	RBL	5
Green	GRN	5
Red	RED*	4

■ INDICATES STOCKED ITEMS

ADDITIONAL INFO

- For custom light output, contact your sales associate
- *Color Temperature Amber and Red are not Turtle Friendly; see our Turtle Friendly fixtures for more information

FEATURES

- Overdesigned heat sink and thermal management for longevity and consistency
- Dedicated LED fixtures
- Machined Metal Ingot, not Cast Material
- Proprietary design-enhanced and robust driver technology
- Remarkably tight binning process. 2-step MacAdam ellipse to ensure consistent light output and no variant light
- Surge protection built into every driver

