# VISIONARY SERIES

V3 | SPOT LIGHT

## **CATEGORY**

**LED Spot Light** 

## LED LIFE EXPECTANCY | WARRANTY

TM-21 data: Greater than 80,000 hours (20+ years at 8 hours a day) 20 Year Warranty


We run our fixtures 40% cooler than LM-80 testing standards





| APPLICATION   | CONSTRUCTION                      | DRIVER SYSTEM   | INPUT POWER | INSTALLATION                   | LEAD WIRES   | CRI | CERTIFICATION                               |
|---|-----------------------------------|-----------------|-------------|--------------------------------|--|-----|---|
| Up Light<br>Shadowing<br>Wall Wash<br>Silhouette<br>Architectural Accents | 6061 Aluminum<br>C360 Solid Brass | External Driver | 10.5-18 VAC | LV180 Ground<br>Stake Included | ULECC 18 AWG<br>Tinned Copper Wire<br>46 Inch Length | 80  | UL1838<br>Low Voltage<br>Landscape Lighting |

#### PRODUCT DIMENSIONS



### BE - WATTS / VA / LUMENS

#### BE - WATTS / VA / LUMENS

20 - 2W/4VA - 190Im

35 - 4W/7VA - 330Im

50 - 6W/10VA - 460Im

75 - 9W/15VA - 620Im

# **BEAM SPREAD & FINISH**


| BEAM SPREAD              | FINISH   |
|--------------------------|--|
| 12°<br>25°<br>40°<br>60° | Architectural Bronze (AB)<br>C360 Solid Brass (BR)<br>Stainless Aluminum (SSA) |

#### POWER CONSUMPTION

| COLOR TEMPERATURE | VA                      | VA  | VA | VA |  |  |  |
|-------------------|-------------------------|-----|----|----|--|--|--|
| 3000K             | 4                       | 7   | 10 | 15 |  |  |  |
| 2700K             | 4                       | 7   | 10 | 15 |  |  |  |
| 5000K             | 4                       | 7   | 10 | 15 |  |  |  |
| AMB*              | 6                       | 10  | 11 | 17 |  |  |  |
| BLU               | 6                       | 11  | 11 | 17 |  |  |  |
| RBL               | 6                       | 10  | 11 | 17 |  |  |  |
| GRN               | 6                       | 11  | 11 | 17 |  |  |  |
| RED*              | 4                       | 8   | 7  | 13 |  |  |  |
| FSA**             | N/A                     | N/A | 9  | 15 |  |  |  |
| LVR**             | N/A                     | N/A | 10 | 16 |  |  |  |
| INDICATES STOC    | INDICATES STOCKED ITEMS |     |    |    |  |  |  |

## **PHOTOMETRICS**

\*Complete IES files furnished upon request.



#### **FEATURES**

- Compression lens technology; no glue
- Overdesigned heat sink and thermal management for longevity and consistency
- Dedicated LED fixtures
- Machined Metal Ingot, not Cast Material
- Proprietary design-enhanced and robust driver technology
- Remarkably tight binning process. 2-step MacAdam ellipse to ensure consistent light output and no variant light
- Surge protection built into every driver
- Lumen levels-fixtures tested with shrouds

# ADDITIONAL INFO

- Built in USA | Tampa, FL
- For custom light output, contact your sales associate
- \*\*Fuchsia and Lavender require additional lead time
- \*Color Temperature Amber and Red are not Turtle Friendly; see our Turtle Friendly fixtures for more information









