

# DECK LIGHT MICRO II

## DL II MICRO | DECK LIGHT

### CATEGORY

LED Deck Light

### LED LIFE EXPECTANCY | WARRANTY

TM-21 data: Greater than **80,000 hours** (20+ years at 8 hours a day)

20 Year Warranty

We run our fixtures **40%** cooler than LM-80 testing standards



SSA



BLK



AB



WHT





BR

### SPECIFICATIONS

APPLICATION	CONSTRUCTION	DRIVER SYSTEM	INPUT POWER	INSTALLATION	LEAD WIRES	CRI	CERTIFICATION
Decks Railings Wall Mount Step Lighting Fences	6061 Aluminum C360 Solid Brass	Internal Driver	10.5-18 VAC	Mounting Bracket Included	UL1015 22 AWG Tinned Copper Wire 60 Inch Length	80	UL1838 Low Voltage Landscape Lighting

### PRODUCT DIMENSIONS



### WATTS / VA / LUMENS

WATTS / VA / LUMENS

1W/2VA - 115lm

### BEAM SPREAD & FINISH

BEAM SPREAD	FINISH
130°	Architectural Bronze (AB) Black (BLK) C360 Solid Brass (BR) Stainless Aluminum (SSA) White (WHT)

### POWER CONSUMPTION

COLOR	TEMPERATURE	VA
	3000K	2
	2700K	2
	5000K	2
	AMB*	1
	BLU	2
	RBL	2
	GRN	2
	RED*	1

INDICATES STOCKED ITEMS

### PHOTOMETRICS

\*Complete IES files furnished upon request.

### FEATURES

- Overdesigned heat sink and thermal management for longevity and consistency
- Dedicated LED fixtures
- Machined Metal Ingot, not Cast Material
- Proprietary design-enhanced and robust driver technology
- Remarkably tight binning process. 2-step MacAdam ellipse to ensure consistent light output and no variant light
- Surge protection built into every driver

### ADDITIONAL INFO

- Built in USA | Tampa, FL
- For custom light output, contact your sales associate
- \*Color Temperature Amber and Red are not Turtle Friendly; see our Turtle Friendly fixtures for more information

