

SATURN HALO SERIES

S1 HALO | SATURN SERIES



BLK



BR

CATEGORY

Specialty LED Light | LED Water Light

LED LIFE EXPECTANCY | WARRANTY

TM-21 data: Greater than **80,000 hours** (20+ years at 8 hours a day)


20 Year Warranty

We run our fixtures **40%** cooler than LM-80 testing standards

SPECIFICATIONS

APPLICATION	CONSTRUCTION	DRIVER SYSTEM	INPUT POWER	INSTALLATION	LEAD WIRES	CRI	CERTIFICATION
Up/Down Light Shadowing Wall Wash Silhouette Architectural Accents	6061 Aluminum C360 Solid Brass	Internal Driver	10.5-18 VAC	See features section for installation details	ULECC 22 AWG Tinned Copper Wire 46 Inch Length	80	UL1838 Low Voltage Landscape Lighting IP69

PRODUCT DIMENSIONS



BE - WATTS / VA / LUMENS

BE - WATTS / VA / LUMENS

20 - 1W/2VA - 130lm

BEAM SPREAD & FINISH

BEAM SPREAD	FINISH
12°	Black (BLK) C360 Solid Brass (BR)
25°	
40°	
60°	

POWER CONSUMPTION

COLOR	TEMPERATURE	VA
Yellow	3000K	5
Light Yellow	2700K	5
White	5000K	5
Amber	AMB*	6
Blue	BLU	5
Blue	RBL	5
Green	GRN	5
Red	RED*	4

INDICATES STOCKED ITEMS

FEATURES

- Compression lens technology, no glue
- Overdesigned heat sink and thermal management for longevity and consistency
- Dedicated LED fixtures
- Machined Metal Ingot, not Cast Material
- Proprietary design-enhanced and robust driver technology
- Remarkably tight binning process. 2-step MacAdam ellipse to ensure consistent light output and no variant light
- Surge protection built into every driver
- **BLACK MODEL ONLY** is suitable for installation in: fresh water, fish ponds, fish tanks
- **BRASS MODEL ONLY** is suitable for installation in: fresh water, **NOT** suitable for fish ponds or fish tanks.
- No chlorine/harsh chemicals

PHOTOMETRICS

*Complete IES files furnished upon request

ADDITIONAL INFO

- Built in USA | Tampa, FL
- For custom light output, contact your sales associate
- *Color Temperature Amber and Red are not Turtle Friendly; see our Turtle Friendly fixtures for more information

